

### **Model: Model C-JB150ZX – Hydraulic Tipper**

- Motor, controller (w): 72V1500W
- (Nameplate 3900W)
- Hydraulic Dump: **Yes**
- Battery: 6 by Lead-Acid 72V58Ah
- Charging Time: 6-8 hours
- Range Per Charge: 66km
- Front Brake: Disk
- Rear Brake: Drum
- Tyres: Mountain Type
- Front and Rear 4.0-12
- Max Speed: 42km/h
- Max Load 543 Kgs
- Double Layer Structure Frame
- Gross Vehicle Mass: 270kg
- Ground clearance: ≥150mm
- Minimum turning radius: 4m
- Rated loading capacity: 500kg
- Max speed: 25km/h in Low and 42km/h in High
- Maximum climbing slope: ≤ 25°
- Economic speed range: Low - 66km and High - 52km
- Headlight: LED
- Hydraulic Oil Pump: 1200w
- High, Medium and Low - Speed function
- Overall Dimensions: 2868mm(L) x1175mm(W) x1435mm(H)
- Wheelbase: 2035
- Wheel Track: 950mm
- Cargo Box Size (mm) 1500×1100×435 With Drop Down Sides.
- Strong Power, Smooth Start, Low Electro Magnetic Noise
- Multifunctional Highlight Instrument Panel, Colour Screen Display
- Driving Data Is Clear at A Glance
- Thick Outer Spring Shock Absorption
- Battery charging cable



### Model C-ZJ150 – Manual Tipper

- ❖ Motor, controller (w): 72V1000W
- ❖ (Nameplate 2800W)
- ❖ Manual load bed tilt with drop down sides: **Yes**
- ❖ Battery: 6 by Lead-Acid 72V45Ah
- ❖ Charging Time: 6-8 hours
- ❖ Range Per Charge: 62-74km
- ❖ Front Brake: Disk
- ❖ Rear Brake: Drum
- ❖ Tyres: Mountain Type
- ❖ Front and Rear 4.0-12
- ❖ Max Speed: 35km/h
- ❖ Max Load 450 Kgs
- ❖ Double Layer Structure Frame
- ❖ Gross Vehicle Mass: 197kg
- ❖ Ground clearance:  $\geq 150\text{mm}$
- ❖ Minimum turning radius: 4m
- ❖ Maximum climbing slope:  $\leq 20^\circ$
- ❖ Economic speed range: Low - 74km and High - 62km
- ❖ Headlight: LED
- ❖ High, Medium and Low - Speed function
- ❖ Multifunctional Highlighted Instrumental Panel
- ❖ Comfortable Seat
- ❖ Strong Power, Smooth Start, Low Electro Magnetic Noise
- ❖ Driving Data Is Clear at a Glance
- ❖ Thick Outer Spring Shock Absorption
- ❖ Front tyre specifications 3.5- 12
- ❖ Rear tire specifications 3.75-12
- ❖ Double Layer Structure Frame
- ❖ Overall Dimensions: 2853mm(L) x1180mm(W) x1302mm(H)
- ❖ Wheelbase: 1916
- ❖ Wheel Track: 950mm
- ❖ Cargo Box Size (mm) 1500×1100×300 With Drop Down Sides and Tail Gate.

